PREMIUM MOTOR OIL

PREMIUM MOTOR OIL

Aimol produces high-quality lubricants for automotive use, for motorsports and for every industrial application.

Applying all available technologies, which we significantly improved in the last 30 years, we can guarantee ‘friction-free’ performance of transport and industrial equipment. Aimol guarantees reliable high-quality products for all your machineries and engines.

ENGINE

SAHARA

Mineral motor oil designed for gasoline and diesel engines of older types operating in (very) hot climates in which OEM's recommend season oil change.

API-services SA/SB/CA
Available grades: SAE 40, SAE 50, SAE 60

ENGINE

MOTOR OIL SF/CC

Mineral motor oil developed for light to heavy loaded gasoline engines as well as diesel engines without turbo charging and stationary engines.

API-services SF/CC
Performance levels Ford M2C-153C; GM P 6085-M; MB 226.1; MIL L-46152C /L-2104B; CCMC G2/D1
Available grades: SAE 30, SAE 40, SAE 50, SAE 15W-40, SAE 20W-50

ENGINE

MOTOR OIL HD S3

Mineral motor oil for light and heavy duty gasoline and diesel engines, as well as stationary engines. Also suitable for use when diesel fuel has a higher sulphur content.

API-services CD/SF
Performance levels MIL-L-2104C / MIL-L-46199B; Allison C-4; Caterpillar TO-2/Series 3
Available grades: SAE 10W, SAE 30, SAE 40, SAE 50

ENGINE

MOTOR OIL HD S3 EXTRA

Mineral motor oil developed for light to heavy loaded gasoline and diesel engines with or without turbo charging and stationary engines. Also suitable for use when diesel fuel has a higher sulphur content.Complies with API CF-2 requirements which is often prescribed for 2 stroke diesel engines.

API-services SF/CF; API CF-2 (SAE 30, 40, 50);
Performance levels CCMC G2/D4/PD1; MIL L-2104E; MIL L-46152 B/C; Ford ESE-M2C-153C (SF/CD); MB 227.0
Available grades: SAE 10W, SAE 20W-20, SAE 30, SAE 40, SAE 50

ENGINE

PREMIUM MOTOR OIL

High quality universal motor oil.

API-services SL/CF
Performance levels ACEA A3/B3, ACEA A3/B4 (04); VW 500.00/505.00(10W); VW 501.01/505.00(15W & 20W); MB 229.1
Available grades: SAE 10W-30, SAE 10W-40, SAE 15W-40, SAE 15W-50, SAE 20W-50

ENGINE

STREETLINE

Semi-synthetic motor oil for gasoline and diesel engines of passenger cars, vans.

API-services SM/CF
Performance levels ACEA A3/B3/B4; MB 229.1; Volkswagen 500.00/505.00; BMW Special Oil; Porsche
Available grades: SAE 10W-40, SAE 15W-50

ENGINE

STREETLINE 5W-40

Full synthetic motor oil for gasoline and diesel engines of passenger cars, vans.

API-services SN/CF

Performance levels ACEA A3/B3/B4; MB 229.1/229.3; Volkswagen 502.00/505.00; BMW LL-01; Porsche

ENGINE

SPORTLINE 0W-40

Top quality full synthetic motor oil of the latest generation, for the newest gasoline and diesel engines of passenger cars, vans, with catalytic converter and with or without turbocharger.

API-services SL/CF

Performance levels ACEA A3/B4; MB 229.3/229.1; BMW Long life; Volkswagen 02.00/503.01/505.00; Porsche

ENGINE

SPORTLINE 5W-50

Full synthetic motor oil for use in high power/high rpm engines/sport cars.

API-services SN/CF

Performance levels ACEA A3/B3/B4; MB 229.1/229.3; BMW LL-01; Volkswagen 502.00/505.00, Renault RN0700/RN0710

ENGINE

SPORTLINE 10W-60

Full synthetic motor oil for use in high power/high rpm engines/sport cars.

API-services SM/CF

Performance levels ACEA A3/B4(08); MB 229.1; BMW Special Oil; VW 500.00/505.00; Porsche

ENGINE

PROFI LINE 5W-30

A range of full synthetic motor oils for the latest generation gasoline engines.

Proline V ACEA C3/A3/B4; VW504.00/507.00; MB 229.51; BMW LL04; Porsche C30.

Proline M/B MB 229.31/229.51; BMW LL01/LL04; API SL/CJ; ACEA C3/A3/B4; VW502.00/505.00/505.01; Ford M2C-917A.

Proline J GM Dexos-1 / LL-A-025/6094M/4718M; ILSAC GF5; API SN-RC .

Proline F Ford WSS-M2C-913C / WSS-M2C-912A+913A/B; API SL

ENGINE

AIMOL TURBO

Heavy Duty all-season, mix-fleet engine oil.

API-services CG-4/CF-4/CF/SJ

Performance levels ACEA E2/A2/B3 and A3 (98), Volvo VDS, MB 228.1; 229.1, Volkswagen 501.01/505.00

Available grades: SAE 10W-30, SAE 15W-40

ENGINE

TURBO LD

Heavy duty all-season long drain diesel engine oil.

API-services CI-4/CH-4/SL;

Performance levels ACEA A3/B3/B4/E3/E5/E7; M.A.N. 3275 (271); Volkswagen 501.01/505.00; MTU Type 2; ZF-TE-ML 02C/03A/04B/04C/07C; Renault RLD-2; MB 228.3/228.1/229.1; Volvo VDS II&III (15W40 official approval for VDS III); Global DHD1; Allison C-4; Mack EO/M Premium Plus; Cummins 20071/76/78 – 20072/77; Caterpillar ECF-2

Available grades: SAE 10W-30, SAE 15W-40

ENGINE

TURBO XLD SAE 15W-40

Universal SHPD (Super High Performance Diesel) oil.

Performance levels ACEA E5/E7/E9; Cummins CES 20081; MB 228.31; Mack EO-O Premium Plus; API CJ-4/SM; Caterpillar ECF-3 / ECF- 2/ ECF-1; MTU type II; DDC PGOS 93 K 218; Volvo VDS-4; Global DHD-1; Renault RLD-3; MAN M3275

ENGINE

TURBO LD PLUS SAE 10W-40

Synthetic technology based motor oil for all-season use in heavy diesel engines. Also suitable for gasoline, LPG and light diesel engines.

API-services SL/CI-4 plus/CI-4/CH-4/CG-4/CF-4/CF;

Performance levels ACEA A3/B3 and E7 (08); Volvo VDS II & III; MB 228.3/229.1; MAN 3275 and 271; Global DHD1, DLD1, DLD3; VW 500.00/505.00; Allison C-4; MTU Type 2; Mack EO/M Plus; ZF-TE-ML 04C/07C SAE 10W-40

ENGINE

TURBO SYNTH TFE 10W-40

High performance motor oil for all-season use in mixed fleet and heavy-duty truck diesel engines EURO-2/3

API-services CI-4plus/CI-4

Performance levels ACEA E4/E7(07)/E4(08); Mack EO/M Plus; Renault RXD/RLD 2; Deutz DDQ-III; MB 228.5; Volvo VDS 2 & 3; ZF-TE-ML 04C/07C; Scania LDF; Allison C-4; Global DHD1; MAN 3277 & 271; MTU Type 3; DAF HP-2

ENGINE

TURBO SYNTH TFE 5W-40

Ultra high performance motor oil for all-season use in heavy-duty truck diesel engines

API-services CI-4plus/CI-4/CF

Performance levels ACEA E3/E4/E5/E7; Mack EO/M Plus; MB 228.5; Volvo VDS 2 & 3; CAT ECF-1; Deutz DDQ-III; Scania LDF; MAN 3277; MTU/DDC Type 3; Renault RXD/RLD-2

GEAR

GEAR OIL GL1

Mineral gear oil for various transmission applications.

Performance levels Premium General Purpose GL-1
Available grades: SAE 90, SAE 140

GEAR

GEAR OIL GL- 4

Mineral gear lubricating for mechanical transmissions with special EP additives.

API-services GL4; MIL-L-2105
Available grades: SAE 80W-90

GEAR

AXLE OIL GL-5

Hypoid mineral gear lubricant for mechanical transmissions and/or differentials.

80W-90 / 85W-140: API GL-5; MIL-L-2105D; Mack GO-G; ZF TE-ML 05A,12A; MAN 342 N / MAN 342 typ M-1; MT-1
85W-90: API GL-5; MIL-L-2105D; MB 235.0; ZF TE-ML 05A,07A,08,16F,17B, MAN 342N/ MAN 342 typ M-1; Volvo 97310; RVI 03-80-4003; MT-1
Available grades: SAE 80W-90, SAE 85W-140, SAE 85W-90

GEAR

AXLE OIL GL-5 75W-90

Hypoid gear oil on synthetic basis for high loaded mechanical transmission and/or differentials which require API GL-5 oil.

API-services GL-5
Performance levels ZF: TE ML 05A/12A; Mil L-2105D; MAN 342N / 342 type M-1; Mack GO-G

GEAR

AXLE OIL GL-5 LS SAE 85W-90

Hypoid mineral gear lubricant for transmissions which require limited slip additives.

API-services GL5
Performance levels Mil L-2105D; ZF TE-ML 05C/12C/16E; MT-1; Case MS 1317 (85W-140)

GEAR

SUPERGEAR GL 4/5 SAE 80W-90

Premium-quality transmission oil especially developed for universal use in the manual transmissions and differentials of passenger cars and trucks; total drive line (TDL).

API-services GL3/GL4/GL5 and MT-1
Performance levels MIL-L-2105 B/C/D/E, ZF TE-ML 01, 02B, 05A, 07A+B, 08, 12E, 16B+C+D, 17B; MB 235.0; Scania STO-1 and 2; Volvo 97310; MAN 341ML, 342ML, 3341ML

TRANSMISSION

ATF DEXRON® II

Multipurpose fluid for heavy duty equipment transmissions and hydraulic systems.

Performance levels GM (former Dexron® II); Allison C-4;
Renk; MB 236 1/5/7/9; ZF TE ML 09/11/14;
Voith G 607/H55.6335.34;
Vickers D 2882 / 35 VQ 25; Denison HF-0;
Ford M2C 166-H / 138 CJ / 33F- G;
Man 339D / Man 339 V1/ZI, Caterpillar TO-2.

TRANSMISSION

ATF DEXRON® III

Multipurpose fluid for use in transmissions, hydraulic systems and heavy duty equipment.

Performance levels GM: DEXRON® III (F en G); Allison: C-4;
Ford: MERCON; Daimler Chrysler 236.1/5/9;
Voith G 607/ H55.6335.34;
ZF TE ML 03D/04D/09B/11A/14B/17C;
MAN 339F / MAN 339 V1 & 339 Z1;
DEXRON® II-E, II-D, B, AQ-ATF type A;
MERCON M2C 138-CJ, M2C 166-H;
Caterpillar TO-2; Renk Doromat; Volvo 97335 -12.

GEAR

CATGEAR

Mineral gear lubricant for mechanical transmissions, differentials, final drives and hydraulic systems.

API-services CF, CF-2
Performance levels CAT TO-4; ZF TE ML 01, 03;
Allison C-4; Komatsu KES 07.868.1
Available grades: SAE 10W, SAE 30

TRANSMISSION

ATF MULTI

Allround Synthetic Automatic Transmission Fluid.

Performance levels Allison C-4 & TES 295; ZF TE ML 09X- 11B- 14B;
Toyota T-III, T-IV; Mercon, Mercon V;
Hyundai and Mitsubishi SP, SP- II and III;
MAN 339 type D & F Z1/V1 & Z2;
Isuzu Saab 93 165 147;
ATF 7045E, ATF 1375.4 and LA 2634;
Nissan Matic D, J and K; Mazda M-III;
Idemitsu K7; Caterpillar TO-2; MB 236.1…236.9;
Dexron® II and III;
Volvo 1161540 and Audi G-005-025-A;
ATF LT 71141; BMW LT-2;
Ford M2C-138CJ, 166H, 202B; JASO M 415 1A;
JATCO 3100 PL 085; JASO M 415 1A; JATCO 3100 PL 085;
GM 9986195, JWS 3309/ 3314/3324;
Subaru K0410Y0700

GEAR

HYTRAN UTTO SAE 10W-30

Mineral gear lubricant for mechanical transmissions and differentials.

Performance levels API: GL4; FNHA-2-C-201.00;
Ford M2C 134 A/B/C/D; Ford M2C 86-B/C;
Ford M2C 41B, M2C 48B, M2C 53A;
MF M1127/1129A/1141/1135/1143/1145;
Case MS 1204-1207, 1209 ,1210, JIC 143/185;
WB 101; MAT3525;
Renk Doromat 873, 874A, 874B;
Fiat, Renault, Same, Landini, Fendt, McCormick;
John Deere JDM J20C, J20D; White Farm Q1826;
Deutz-Allis, DD-Allison C3/C4; Power Fluid 821XL;
Caterpillar TO-2; ZF-TE-ML-03E/03F/05E/05F/06K;
Sperry-Vickers I-286-S, M-2950-S; Kubota UDT;
Komatsu Dresser B-06-0001 / B-06-0002

COOLING

FREEZE BS

Good quality, single phase, ethylene glycol based antifreeze.

Performance levels BS 6580; AFNOR NF R15-601; ASTM D3306; ASTM D4656; SAE J 1034

COOLING

FREEZE G12+

Superior quality, single phase, ethylene glycol based antifreeze.

Performance levels VW/Audi/Seat/Skoda TL-774F (G12+); VW/Audi/Seat/Skoda TL-774F (G12+); Mercedes Benz 325.2; MAN 248 & 324; Ford WSS-M97B44-C; GM 1899 M, US 6277 M; Opel GM QL 130100; Leyland Trucks LTS 22 AF 1; Mack 014GS 17004; Renault Type D; Volvo; Chrysler MS 9176; Cummins 85T8-2 & 90T8-4; John Deere H 24 B1 & C1; JASO M325; NATO S-759; BS 6580; ASTM D3306/ D4656/ D4985

COOLING

SUMMER COOLANT

Universal Summer Coolant.

Performance levels BS 6580, BR-637, SAE J1034; Cummins; Man 324 Typ N; Fiat/Iveco; ASTM D3306/D4656; AFNOR NFR 15-601; MTU MTL 5048

Avialable frost protections: -18 °C, -26 °C, -36 °C

BRAKE

BRAKE FLUID DOT 3/4

Synthetic hydraulic brake & clutch fluid.
SAE J 1703 / SAE J 1704; ISO 4925;
FMVSS 116 DOT 3 and DOT 4

INDUSTRIAL

HYDRAULIC OIL HLP

High performance anti-wear hydraulic oil.
DIN 51524 Part-2 (HLP); AFNOR NF E 48603 HM; VDMA 24318; US Steel 127; Cincinnati Milacron (for HLP 32, 46 and 68); Vickers I-286-S, M-2950-S; FZG A/8.3/30>12 (ISO-VG 46 and higher); FZG A/8.3/90=12 (ISO-VG 15/22/32); ISO class L=HM (according ISO 6743/4); Thyssen TH-N-256132

Available ISO-VG grades: 10, 15,22, 32, 46, 68

INDUSTRIAL

HYDRAULIC OIL HLP-ZF

High performance anti-wear zinc free hydraulic oil.
ISO-L DAA/DAB/DAG/DAH; DIN 51524 HLP; Vickers I-286-S; AFNOR NFE 48-603 cat. HM

Available ISO-VG grades: 32, 46, 68

INDUSTRIAL

HYDRAULIC OIL HVI-P

High viscosity index hydraulic oil.
HLP DIN 51524 Part-3 (HVLP);
ISO classification L-HV (acc. ISO 6743/4);
Vickers I-286-S / M-2950-S;
Cincinnati Milacron P86/P69/P70 (ISO-VG 32/46/68);
FZG A/8.3/90>12 (46 & 68); VDMA 24318;
FZG A/8.3/90=12 (32); US Steel 126/127;
Afnor NF E 48603 (HV); Thyssen TH-N-256132

Available ISO-VG grades: 15, 22, 32, 46, 68

INDUSTRIAL

HYDRAULIC OIL HVI-ZF

High viscosity index zinc-free hydraulic oil.
DIN 51524 Part-3 (HVLP); AFNOR NF E 48603 HV;
VDMA 24318; German Steel SEB 181222;
Denison HF-2; US Steel 127; Cincinnati Milacron;
Sperry Vickers; Clearness code (ISO 4406)-14/12/10

Available ISO-VG grades: 32, 46, 68

INDUSTRIAL

INDO GEAR OIL

Industrial gear oil with EP characteristics.
Timken OK Load 75 lbs; CLP DIN 51517 part 3 CLP;
US Steel 224; AGMA 250.04 EP/9005-D94;
FZG gear test >12; David Brown S1.53.101

Available ISO-VG grades: 68, 100, 150, 220, 320, 460

INDUSTRIAL

COMPRESSOR OIL P

Mineral based compressor oil for general use.
DIN 51506: VBL, VCL & VDL;
ISO-L: DAA/DAB/DAG/DAH; DIN 51524: HLP;
Vickers: I-286-S; AFNOR: NFE 48-603 cat. HM

Available ISO-VG grades: 100, 150, 220

INDUSTRIAL

COMPRESSOR OIL S

Mineral based compressor oil for general use and for screw air compressors.
DIN 51506: VBL, VCL and VDL; ISO-L: DAA/DAB/DAG/DAH; DIN 51524: HLP;
Vickers: I-286-S; AFNOR: NFE 48-603 cat. HM

Available ISO-VG grades: 46, 68

INDUSTRIAL

SLIDEWAY OIL

Mineral based slideway oil for both metal as well as plastic slideways.
DIN 51517 part 3: CLP; DIN 51524 part 2: HLP;
Cincinnati Milacron: P47 (AIMOL Slideway Oil 68)
P50 (AIMOL Slideway Oil 220)

Available ISO-VG grades: 68, 220

These are just a few examples of mainstream industrial lubricants. We have a complete range of highly specialised products available for every industrial application.
See our website www.aimol.nl and/or ask us.

CAR CARE

AIMOL has a large range of car care and support products. Some examples are:

Products:
- Penetrating Oil
- Silicon Spray
- Gear Grease
- Copper Spray
- Brake Cleaner
- Bitume Cleaner
- Leather Cleaner
- Textile Cleaner
- Mosquito Cleaner
- Tyre Cleaner
- AC Cleaner

Our range is much larger, so if you cannot find the product you are looking for: ask us!

Disclaimer

Because of continuous product research and development, the information within this publication is subject to change without any notification. Although every effort is made to ensure accurate information, Anglo International Mining B.V. accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text.

TIME FOR QUALITY TIME FOR AIMOL

The Aimol and Aimol-M products have an excellent reputation in the market of high-quality lubricants. If you want to experience this reputation, then please contact us. We shall take all the time needed to handle your request.

Haringvliet 543
3011 ZP Rotterdam
The Netherlands
www.aimol.nl
Tel: +3110 282 79 27
Fax: +3110 282 79 26